



TECHNICAL DATA SHEET

GRODAL CIRCULATING 12 CIRCULATING OIL

DESCRIPTION

Grodal Circulating 12 is blended from high quality paraffin base stocks and effective EP additive package designed to minimize wear. It is a blend of high viscosity index chemically stable base oil and specially selected anti wear, anti oxidant, anti rust additives.

APPLICATION

Grodal Circulating 12 lubricant is recommended for use in enclosed gear boxes conveyers, hydraulic systems and chain drives machine tools etc.

BENEFITS

- Extreme pressure properties to minimise wear.
- Long oxidative and thermal service life.
- Protection against rust and corrosion.
- Resistance to foaming.

TYPICAL TECHNICAL DATA

Colour & Appearance	:	Pale Clear Liquid
Sp.Gravity @ 30°C	:	0.83
Flash Point COC	:	120 Min.
Viscosity @ 40°C	:	12.0 cSt.
Viscosity Index	:	98
Pour Point °C	:	- 12

ADVICE

Store at ambient temperature and away from direct contact of fire. Avoid contact with water.

SAFETY

This oil is unlikely to present any significant health or safety hazard when properly used in the recommended application as well as good standards of industrial and personal hygiene is maintained.

Issued on : 06.08.2011

Supersedes all earlier