



TECHNICAL DATA SHEET

GRODAL CIRCULATING 32 CIRCULATING OIL

DESCRIPTION

Grodal circulating 32 oil is designed to give extended service life, Grodal circulating 32 oil is applied in a broad range of system that are operated under high impact and high shock.

Grodal circulating 32 oil is formulated to address environmental concerns; Grodal circulating 32 oil is free of zinc and does not contain phenol.

Grodal circulating 32 is formulated with highest quality petroleum base oil and which is selected for both their natural stability and for compatibility with high performance components. Exceptional rust and oxidation resistance are results of unique formulation of selected base oil and additives.

APPLICATION

Grodal circulating 32 is useful where circulating oil must have characteristics of a high viscosity index.

Grodal circulating 32 oil is generally for use in lubricating oil circulating system that is well engineered and is protected from leakage or contamination which would require frequent oil replacement.

Hydraulic systems of all types, including hydraulic motors, pumps and multi service system, also lubrication of bearings, spindles, gears and non critical ways.

BENEFITS

Essential to long, safe service life for both the oil and expensive machines are therecharacteristic of Grodal circulating 32 oil.

- Resistance to oxidation and the formation of deposits.
- Protection against wear.
- Fast separation from water.
- Protection against rust and corrosion.
- Compatability with seal material leakage.
- Environmentally friendly (no zinc, phenol)

TYPICAL TECHNICAL DATA

Colour & Appearance	:	Pale to brown liquid
Sp.Gravity @ 30°C	:	0.87
Flash Point	:	200 °C
Viscosity @40 °C	:	32 CST
Pour point	:	- 9
Foam test	:	passes
Demulsibility	:	passes
Copper corrosion	:	1a
Rust test	:	passes

RECOMMENDATIONS

Store in a cool dry, well ventilated area out of direct sunlight. Avoid Sparks, flames and other ignition sources. Store away from incompatible materials such as material that support combustion.

SAFETY

This oil is unlikely to present any significant health or safety hazard when properly used in the recommended application as well as good standards of industrial and personal hygiene is maintained.

Issued on : 4.08.2011

Supersedes all earlier

GRAUER & WEIL (INDIA) LTD. (Lube Division)

Registered Office : 'Growel House' , Akurli Road, Kandivli (E), Mumbai - 400 101, India

Tel. : 91 - 22 - 66993000 , Fax : 91 - 22 - 669930101/11,

E-mail : lubricants@growel.com, Website : www.growel.com