

GRODAL HYDRA 100

Hydraulic Oil

PRODUCT DESCRIPTION

Grodal Hydra 100 is a light colored, premium quality, anti wear hydraulic fluid formulated from high quality paraffin base stock with excellent stability, good resistance to oxidation and moisture with high natural viscosity index. It contains specifically selected anti-foamant, anti-rust, anti-oxidant and zinc type anti wear agent.

BENEFITS

- Good oxidation stability for long service life.
- Resistance to sludge and varnish deposits
- Minimizes wear and scoring
- Corrosion and wear protection for components

APPLICATIONS

Grodal Hydra 100 is formulated as a superior heavy duty anti wear hydraulic oil for use in modern high pressure hydraulic systems. It also provides good anti-rust and water separation properties. It acts as a medium for transmitting power. It is recommended to handle the most severe hydraulic applications and satisfy many other lubrication applications. This product meet the following specifications :

Vickers Vane Pump Test

Denison HF0, HF1 and HF2

DIN 51524 PART 2 and PART 3

PRODUCT RECOMMENDATIONS

Grodal Hydra 100 is recommended for all industrial and mobile hydraulic system application. Due to incompatibility of silver and zinc containing oils, Grodal Hydra 100 should not be used in systems incorporating silver coated components.

PRODUCT MAINTENANCE

Grodal Hydra 100 is designed for long service life but it is known that all hydraulic oils eventually degrade due to the effect of oxidation. The symptoms of oil oxidation are an increase in viscosity, increase in acidity or the formation sludge.

TYPICAL SPECIFICATION

Colour & Appearance	: Yellow Clear Liquid
Sp.Gravity @ 30°C	: 0.88
Flash Point COC °C	: 210 Min.
Viscosity @ 40°C	: 100.0 cSt.
Viscosity Index	: 96
Pour Point °C	: - 3

*Issued on : 07.03.2008
Supersedes all earlier*