

## TECHNICAL DATA SHEET

# **GRODAL GEAR 220**

INDUSTRIAL GEAR OIL

#### **DESCRIPTION**

Grodal Gear 220 is blended from high quality paraffin base stocks and effective EP additive package designed to minimize wear of enclosed gears operated under heavy loads.

#### **APPLICATION**

Grodal Gear 220 lubricants are recommended for a variety of gears including spur, bevel, helical, worm and industrial hypoid gear cases on mobile contractor type equipment, cement mills, crushers, hoists, conveyers, winches and marine equipments.

#### **BENEFITS**

- Extreme pressure properties to minimise wear.
- Long oxidative and thermal service life.
- Protection against rust and corrosion.
- Resistance to foaming.

#### **TECHNICAL DATA**

Appearance : Brown clear oil
Sp. Gravity @30°C : 0.885 – 0.910
Viscosity @40 °C : 220 cSt.
Viscosity Index : 96

Flash Point COC °C : Above 210

Pour Point °C : -3 Foam test : Pass

### **RECOMMENDATIONS**

Meets the requirements of # AGMA 250.04 # DIN 51517 Part 3 # U. S. Steel 224.

### **ADVICE**

Store at ambient temperature and away from direct contact of fire. Avoid contact with water.

#### **SAFETY**

This oil is unlikely to present any significant health or safety hazard when properly used in the recommended application as well as good standards of industrial and personal hygiene is maintained.

Issued on: 15.04.2010 Supersedes all earlier

GRAUER & WEIL (INDIA) LTD. (Lube Division)

Registered Office: 'Growel House', Akurli Road, Kandivli (E), Mumbai - 400 101, India

Tel.: 91 - 22 - 66993000 , Fax: 91 - 22 - 669930101/11, E-mail: lubricants@growel.com, Website: www.growel.com