



TECHNICAL DATA SHEET

GRODAL RPOB 10

RUST PREVENTIVE

DESCRIPTION

Grodal RPOB 10 is a oil based type of rust preventive. This product leaves oily protective film with significant corrosion inhibition properties.

APPLICATION

Grodal RPOB 10 is a soft oily film coating product. It is recommended for protection of mechanical parts, steel components, machine shop and tool manufacturers. It gives reasonable protection for indoors and outdoors.

BENEFITS

- Easy application
- Provides excellent protection to assemblies.
- Easy removal
- Excellent non staining property
- Good resistance to salt water

TECHNICAL DATA

Colour and Appearance	:	Brown liquid
Sp. Gravity @ 30 °C	:	0.82 - 0.86
K.Viscosity @ 40 °C	:	16 - 17 Cst.
Indoor Protection	:	9 Months
Outdoor Protection	:	3 Months
Film type	:	Oily

RECOMMENDATIONS

Grodal RPOB 10 is recommended to apply by dip method to give a protective film on component. Spray method can also be used for certain applications. This protective film can removed by solvent or suitable alkaline cleaner.

SAFETY

This oil is unlikely to present any significant health or safety hazard when properly used in the recommended application as well as good standards of industrial and personal hygiene is maintained.

Issued on : 21.09.2010

Supersedes all earlier

GRAUER & WEIL (INDIA) LTD. (Lube Division)

Registered Office : 'Growel House' , Akurli Road, Kandivli (E), Mumbai - 400 101, India

Tel. : 91 - 22 - 66993000 , Fax : 91 - 22 - 669930101/11,

E-mail : lubricants@growel.com, Website : www.growel.com