



TECHNICAL DATA SHEET

GRODAL SPINDLE 22

SPINDLE OIL

DESCRIPTION

Grodal spindle 22 is superior quality oil blended with low viscosity mineral base oils and additives.

APPLICATION

Grodal Spindle 22 is suitable in machine tool lubrication. This is designed for use in all types of spindle bearings.

BENEFITS

- High oxidation stability.
- Preventing sludge formation during the operation for long period.
- Excellent wear protection.
- No corrosion.
- Good surface finish.

TYPICAL TECHNICAL DATA

Appearance	:	Pale to brown Liquid
Sp. Gravity @30°C	:	0.81 – 0.85
K. Viscosity @40 °C	:	18 - 26 cst.
Flash Point	:	150 °C
Pour point	:	- 12

ADVICES

Store at ambient temperature and away from direct contact of fire. Avoid contact with water.

SAFETY

This oil is unlikely to present any significant health or safety hazard when properly used in the recommended application as well as good standards of industrial and personal hygiene is maintained.

Issued on : 06.08.2011

Supersedes all earlier

GRAUER & WEIL (INDIA) LTD. (Lube Division)

Registered Office : 'Growel House' , Akurli Road, Kandivli (E), Mumbai - 400 101, India

Tel. : 91 - 22 - 66993000 , Fax : 91 - 22 - 669930101/11,

E-mail : lubricants@growel.com, Website : www.growel.com