



GRODAL STCUT GR 3 NEAT CUTTING OIL

DESCRIPTION

GRODAL STCUT GR 3 is superior quality neat oil blended from high flash and low volatility mineral base oils. It contains high EP and antioxidant additives for long life.

APPLICATION

GRODAL STCUT GR 3 is suitable in machine tool lubrication and threading operations. It has been formulated to give excellent anti-wear and EP characteristics to cover a broad range of metal cutting operations.

BENEFITS

- High oxidation stability.
- Preventing sludge formation during the operation for long period.
- Will not give excessive fumes or froth.
- No corrosion
- Good surface finish

TECHNICAL DATA

Appearance	:	Clear Liquid
Sp. Gravity @30°C	:	0.75 – 0.78
Viscosity @40 °C	:	2 - 3 cst.
Flash Point	:	90 °C
Pour Point	:	-6 °C

ADVICE

Store at ambient temperature and away from direct contact of fire. Avoid contact with water.

SAFETY

This oil is unlikely to present any significant health or safety hazard when properly used in the recommended application as well as good standards of industrial and personal hygiene is maintained.

Issued on : 20.06.2011

Supersedes all earlier

GROWEL SIDASA INDUSTRIES PRIVATE LIMITED

Registered Office : 'Growel House', Akurli Road, Kandivli (E), Mumbai - 400 101, India
Tel. : 91 - 22 - 66993000 , Fax : 91 - 22 - 669930101/11, E-mail : growel-sidasas@growel.com,
Website : www.growel.com