

MATERIAL SAFETY DATA SHEET

GROWEL SIDASA INDUSTRIES PRIVATE LIMITED

'Growel House', Akurli Road, Kandivli (East), Mumbai - 400 101, INDIA
Tel : 91-22-66993000 • Fax : 91-22-66993010/11 • E-mail : hq@growel.com

PRODUCT NAME: GRODAL CUTSOL - A

I. INGREDIENTS

MINERAL OIL CAS NO. 64742-52-5 ` EMULSIFIER AND DEFOAMER.

II. PHYSICAL PROPERTIES

- | | | |
|------------------------|---|----------------------|
| 1. APPEARANCE | : | AMBER LIQUID |
| 2. SP. GRAVITY @ 30 °C | : | 0.87 - 0.90 |
| 3. SOLUBILITY IN WATER | : | MILKY WHITE EMULSION |
| 4. ODOUR | : | TYPICAL OIL |
| 5. OTHER (pH) | : | 9 - 10 |

III. FIRE AND EXPLOSION HAZARD DATA

- | | | |
|---------------------------------------|---|---|
| 1. FLASH POINT °C | : | 190 ⁰ C |
| 2. EXTINGUISHING MEDIA | : | FOAM CO ₂ POWDER. WATER MIST SPRAY. |
| 3. SPECIAL FIRE FIGHTING PROCEDURES | : | MOVE CONTAINER FROM FIRE AREA IF IT CAN BE DONE WITHOUT RISK, KEEP RUN-OFF WATER OUT OF SEWERS AND WATER SOURCES. IF WATER POLLUTION OCCURS, NOTIFY APPROPRIATE AUTHORITIES. TO REDUCE THE RISK OF DRUMS BURSTING; SPRAY WITH WATER TO KEEP COOL. WEAR SELF CONTAINED BREATHING APPARATUS. WEAR FULL PROTECTIVE CLOTHING. |
| 4. UNUSUAL FIRE AND EXPLOSION HAZARDS | : | DO NOT ALLOW RUN OFF FROM FIRE FIGHTING TO ENTER DRAINAGE SYSTEM |

IV. HEALTH HAZARD DATA

EFFECTS OF ACUTE EXPOSURE :

- | | | |
|---------------|---|--|
| 1. INHALATION | : | DO NOT INHALE. |
| 2. INGESTION | : | MAY CAUSE IRRITATION TO MOUTH, THROAT IF SWALLOWED |

- 3. SKIN : NO ADVERSE REPORT
- 4. EYES : NO ADVERSE REPORT
- 5. CHRONIC EXPOSURE : NO ADVERSE REPORT
- 6. CARCINOGEN REFERENCE : NO REPORTED REFERENCE

V. EMERGENCY AND FIRST AID PROCEDURES

- 1. INHALATION : MOVE THE EXPOSED PERSON TO FRESH AIR AT ONCE. KEEP THE AFFECTED PERSON WARM AND AT REST. GET PROMPT MEDICAL ATTENTION. WHEN BREATHING IS DIFFICULT, PROPERLY TRAINED PERSONNEL MAY ASSIST AFFECTED PERSON BY ADMINISTERING 100% OXYGEN. PERFORM ARTIFICIAL RESPIRATION IF BREATHING HAS STOPPED.
- 2. INGESTION : NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! RINSE MOUTH THOROUGHLY. DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION IMMEDIATELY.
- 3. EYES : PROMPTLY WASH EYES WITH LOTS OF WATER WHILE LIFTING THE EYE LIDS. CONTINUE TO RINSE FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION.
- 4. SKIN : REMOVE AFFECTED PERSON FROM THE SOURCE OF CONTAMINATION. PROMPTLY ALL AFFECTED SKIN WITH SOAP AND WATER. SEEK MEDICAL ATTENTION.

VI. PRECAUTION FOR SAFE HANDLING AND USE

- 1. SPILL PROCEDURES : INFORM AUTHORITIES IF LARGE AMOUNTS ARE INVOLVED, EXTINGUISH ALL IGNITION SOURCES. AVOID SPARKS, FLAMMES, HEAT AND SMOKING. VENTILATE. STOP LEAK IF POSSIBLE WITHOUT RISK. WEAR FULL PROTECTIVE CLOTHING AND SUITABLE RESPIRATORY PROTECTION. PREVENT THE SOLUTION FROM ENTERING DRAINS OR WATERCOURSES BY USE OF SAND OR EARTH. INFORM LOCAL AUTHORITIES IF THIS CANNOT BE PREVENTED. ABSORB WITH VEMICULITE, DRY SAND OR EARTH AND PLACE INTO SUITABLE CONTAINERS. CLEAN PREFERABLY WITH A SUITABLE DETERGENT. AVOID THE USE OF SOLVENTS WHEN SPILLAGE IS CLERAED FLUSH THE AREA WITH WATER. WASH THOROUGHLY AFTER DEALING WITH THE SPILLAGE.

2. STORAGE AND HANDLING PRECAUTION : STORE AT MODERATE TEMPERATURE IN DRY, WELL-VENTILATED AREA. PROTECT FROM FROST AND EXTREMES OF TEMPERATURE. STORE BETWEEN 5 AND 35 DEG.C.
3. ADDITIONAL INFORMATION : AVOID SPILLING, SKIN AND EYE CONTACT. DO NOT USE IN CONFINED SPACES WITHOUT ADEQUATE VENTILATION AND/OR RESPIRATOR. AVOID CONTACT WITH ALKALIES AND ALKALINE MATERIALS. AVOID CONTACT WITH ACIDS AND ACIDIC MATERIALS. AVOID CONTACT WITH STRONG OXIDISING AGENTS.

VII. CONTROL MEASURES

1. VENTILATION : PROVIDE ADEQUATE GENERAL AND LOCAL EXHAUST VENTILATION.
2. RESPIRATOR : NO SPECIFIC RECOMMENDATIONS MADE, BUT RESPIRATORY PROTECTION MUST BE USED IF THE GENERAL LEVEL EXCEEDS THE OCCUPATIONAL EXPOSURE LEVEL (OEL). EXPOSURE SHOULD BE AVOIDED / CONTROLLED BY VENTILATION OR EXTRACTION. IF EXPOSURE LIMITS ARE LIKELY TO BE EXCEEDED WEAR CHEMICAL RESPIRATOR WITH SUITABLE ORGANIC VAPOUR CARTRIDGE. WHEN SPRAY APPLYING, RESPIRATORY EQUIPMENT WITH POSITIVE AIR SUPPLY SHOULD BE USED IN CASES OF INSUFFICIENT VENTILATION OR WHERE OPERATIONAL PROCEDURES DEMAND IT.
3. EYE PROTECTION : WEAR SUITABLE EYE PROTECTION TO SAFETY GLASSES WITH SIDE SHIELDS ARE RECOMMENDED
4. GLOVES : USE PROTECTIVE GLOVES MADE OF RUBBER OR PLASTIC
5. OTHER PROTECTIVE CLOTHINGS : WEAR APPROPRIATE CLOTHING TO PREVENT REASONABLY PROBABLE SKIN CONTACT. USE ENGINEERING CONTROLS TO REDUCE AIR CONTAMINATION TO PERMISSIBLE LEVEL. PROVIDE EYEWASH STATION AND SAFETY SHOWER.
6. WORK HYGENIC PRACTICES : N.A.
8. ADDITIONAL INFORMATION : N.A.

